

What is claimed is:

1. An undersiding flashing receiver comprising:  
a thin gauge material shaped to have a first leg and a second leg, said  
5 first leg having a top and a bottom and extending longitudinally to form a mounting  
face, said second leg having a first side and a second side, wherein said first side is  
associated with a wall covering and said second side is associated with a removable  
flashing; and  
an intermediate member offsetting said first leg from said second leg.  
10
2. The undersiding flashing receiver according to claim 1, said material is  
plastic.
3. The undersiding flashing receiver according to claim 1, said material is  
15 metal.
4. The undersiding flashing receiver according to claim 1, further  
comprising a plurality of nail openings extending through at least said first leg and  
proximate to said top.  
20
5. The undersiding flashing receiver according to claim 1, further  
comprising a starter strip operatively connected to said second leg.
6. The undersiding flashing receiver according to claim 1, wherein said  
25 intermediate member is rigid.
7. The undersiding flashing receiver according to claim 1, wherein said  
intermediate member is resilient.

8. The undersiding flashing receiver according to claim 1, wherein at least a portion of said second leg is at an angle to said first leg.

9. The undersiding flashing receiver according to claim 8, wherein said  
5 portion of is at an angle to said first leg and to said second leg.

10. The undersiding flashing receiver according to claim 1, wherein at least a portion of said second leg includes a J-shaped channel.

10 11. The undersiding flashing receiver according to claim 10, said J-shaped channel is at a height above said bottom.

12. The undersiding flashing receiver according to claim 11, wherein said J-shaped overlaps at least a portion of the flashing.

15

13. An undersiding flashing receiver comprising:  
a thin gauge material shaped to have a first leg and a second leg, said first leg having a top and a bottom and extending longitudinally to form a mounting face, at least a portion of said second leg being at an angle to said first leg, said  
20 second leg having a first side and a second side, wherein said first side is associated with a wall covering and said second side is associated with a removable flashing;  
a plurality of nail slots extending through said first leg and said second leg, and said plurality of nail slots proximate to said top; and  
an intermediate member offsetting said first leg from said second leg,  
25 wherein said intermediate member is made of a resilient material.

14. The undersiding flashing receiver according to claim 13, said material is plastic.

15. The undersiding flashing receiver according to claim 13, said material is metal.

16. The undersiding flashing receiver according to claim 13, further  
5 comprising a starter strip operatively connected to said second leg.

17. The undersiding flashing receiver according to claim 13, wherein said portion is at an angle to said first leg and to said second leg.

10 18. The undersiding flashing receiver according to claim 13, wherein at least a portion of said second leg includes a J-shaped channel.

19. The undersiding flashing receiver according to claim 18, said J-shaped channel is at a height above said bottom.  
15

20. A method of using an undersiding flashing receiver comprising the steps of:

locating the undersiding flashing receiver along a lower board of a wall adjacent to a roof;

20 securing the undersiding flashing receiver to said wall;  
inserting a flashing into the undersiding flashing receiver;  
securing said flashing to said roof;

at least partially covering said roof and said flashing with roofing material; and

25 connecting an exterior wall covering to the undersiding flashing receiver.